

600 PLUS V2

REFERENCE 00116110 - 600 PLUS V2 - EAN 8422248006316



DESCRIPTION

FEATURES

AEC (Consumo de Energía Anual) (kWh/año)	54,8
EEl class (Class Energy Efficiency)	C
FDE (Efficiency Fluid)	9,3
FDE class (Class Efficiency Fluid)	E
GFE (Fat Filtration Efficiency)	51,9
GFE Class (Class of Fat Filtration Efficiency)	F
Minimum air flow rate (m3 / h)	420
Airflow at maximum speed (m3 / h)	600
Potencia sonora en velocidad mínima (dB)	45
Sound power at maximum speed (dB)	52
Po (electricity consumption in Off mode) (W)	0
Ps (Consumo de Electricidad en modo de Espera) (W)	0
f (Factor Increase in Time)	1,7
EEl (Energy Efficiency)	84,5
QBEP (Air Flow Maximum Efficiency Point) (m3 / h)	285,9
PBEP (static pressure difference in point of maximum efficiency) (Pa)	105
WBEP (electrical power input at maximum efficiency point) (W)	90,1
Engine	INDUCCION
Maximum consumption engine	105W
Maximum pression 190	205
Type of control	CONMUTADOR
Automatic shutdown	NO
Electronic filter saturation indicator	NO
Filter Type	METALICO
Number of grease filters	1
Interior armored	NO
Extraction levels	2
Total power Rush (W)	105
Rated voltage (V)	230
Network Frequency (Hz)	50
Electrical insulation	CLASE I
Width (mm)	355
Depth (mm)	134
Output Diameter (mm)	120

Minimum electric cooking plate distance (mm)	65
A minimum gas hob distance (mm)	65
Installation with outdoor air outlet / recirculation	EXTERIOR
Easy to install	SI
Metal filter	01100000