



IB 5003 BK


IB 5003 BK

Cod. **08074007** EAN **8422248094191**

3 cooking areas:

- Right: 1 area with **Booster function** of Ø280mm of 2.3kW (max. 3kW)
- Front Left: 1 area with **Booster function** of Ø180mm de 1,8kW (max. 2,3kW)
- Rear Left: 1 area with **Booster function** of Ø160mm of 1.2kW (max. 1.5kW)

- Touch Control with acoustic warning
- 9 adjustable power levels + Booster
- Timer function for each area
- Automatic pan detection
- Safety lock
- Residual heat indicator
- Automatic safety switch-off
- 60 cm wide
- Total power 6.5kW**



Code	08074007
EAN	8422248094191
Model	IB 5003 BK
Type	Inducción
Product fiche	
Cooking zones	3
Right front zone: Diameter (mm)	-
Right front zone: Power (kW)	-
Right front zone: Booster (kW)	-
Right front zone: Consumption (Wh/kg)	-
Right rear zone: Diameter (mm)	280
Right rear zone: Power (kW)	2,3
Right rear zone: Booster (kW)	3
Right rear zone: Consumption (Wh/kg)	180,8
Central front zone: Diameter (mm)	-
Central front zone: Power (kW)	-
Central front zone: Booster (kW)	-
Central front zone: Consumption (Wh/kg)	-
Central rear zone: Diameter (mm)	-
Central rear zone: Power (kW)	-
Central rear zone: Booster (kW)	-
Central rear zone: Consumption (Wh/kg)	-
Front left zone: Diameter (mm)	180
Front left zone: Power (kW)	1,8
Front left zone: Booster (kW)	2,3
Front left zone: Consumption (Wh/kg)	184,9
Left rear zone: Diameter (mm)	160
Left rear zone: Power (kW)	1,2
Left rear zone: Booster (kW)	1,5
Left rear zone: Consumption (Wh/kg)	181,7
Energy consumption of the hob (Wh/kg)	182,5
Dimensions	
Product width (mm)	590
Product depth (mm)	520
Product height (mm)	58
Built-in height (mm)	565
Built-in depth (mm)	495
Ventilation slot (mm)	5
Fixing system	Quick-Fix System
Finishing	
Colour	Black
Aesthetic	Rounded
Control	
Control type	Touch
Power selection (+/-)	Centralized
Power levels	9 + Booster
Timer	Yes
Countdown alarm	No
Power management	No
Security	
Safety lock	Yes
Residual heat indicator	Yes
Automatic pan detection	Yes
Automatic safety switch-off	Yes
Protection against liquid spillage	Yes
Electrical connection	
Nominal voltage (V)	220-240
Mains frequency (Hz)	50-60
Max Product power (kW)	6,5